

# PRODUCT DATA SHEET



## Multipurpose Liqid Grease

1/1

Revision: August 9<sup>th</sup>, 2018

DESCRIPTION	ITEM NO.	UNIT
Multipurpose Liqid Grease	92002011	1kg

<b>Description</b>	Multipurpose Liqid Grease
<b>Material</b>	A lubricating grease containing highly-refined mineral oils, polyalphaolefins and additives. Paraffin waxes and Hydrocarbon waxes: 90-95%, 1-Decen, Dimer, hydrogenated: 5-10%.
<b>Properties</b>	Red and viscous lubricating grease. Water-resistant, wear reducing and anticorrosive.
<b>Application</b>	For use in central lubrication systems of ATM abrasive cut-off machines. When exchanging grease container and adjusting the greasing interval, please follow the manual of the ATM cut-off machine.
<b>Health and Safety</b>	Not expected to be a health hazard when used under normal conditions. Avoid prolonged or repeated contact with skin. In case of contact with skin, flush exposed area with water and follow by washing with soap. In a very unlikely case contact with eyes, flush eye with copious quantities of water. If persistent irritation occurs after contact with skin or eye, obtain medical attention.
<b>Personal protection</b>	No special requirements, but it is recommended to wear eye protection, gloves (nitrile rubber).
<b>Respiratory protection</b>	Due to the product's semi-solid consistency and its purpose, generation of mists, dusts or aerosols is unlikely to occur.
<b>Fire protection</b>	Not ignitable, but flammable. Adapt fire protection and firefighting measures to the operating conditions. Do not use water with full jet to extinguish the fire.
<b>Environmental protection</b>	Hazardous for water. Do not allow to enter sewers, surface or ground water. Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. Disposal should be in accordance with applicable regional national, and local laws and regulations. EU Waste Disposal Code (EWC): 12 01 12 spent waxes and fats. Classification of waste is always the responsibility of the end user.
<b>Notes on storage</b>	Use polyolefin receptacles or polyolefin lining in receptacles, if the grease is not stored or used in original container.